



DATA SHEET SPECIFICATIONS

COLD POUR CRACK FILLER # 315

GENERAL:	A pourable, rubberized, asphalt emulsion modified with extenders to give maximum elongation and resiliency in ready to-use product. Designed for filling cracks in asphalt or concrete from 1/4" to 1" wide.
FEATURES & BENEFITS:	Ready to use: on parking lots, airports, streets, playgrounds, etc. Cold Application: No heating necessary. Apply right from container. Great for hot or cold climates. Easy to apply. No fancy tools or experience necessary. Fast Application. In a few hours, you can fill thousands of feet of cracks. Rubberized available, flexible when cured, can withstand pavement expansion and contraction.
WEATHER LIMITATIONS:	For best results, apply on dry surface when temperature is not expected to drop below 50 F for the next 24 hours. Extraneous amounts of water will destroy this crack filler if it has not cured for at least 8 hours.
SURFACE PREPARATION:	Surface must be dry. Blow or sweep-out cracks, removing all vegetation, dust and other debris.
COVERAGE:	120 linear feet 1/4" wide by 1/4" deep per gallon. Coverage will vary with size and depth of cracks.
METHOD OF APPLICATION:	Stir before using. Use as is. May be applied with pour pots or suitable crack sealing applicator. Fill cracks completely. Before material sets-up, remove excess from surface using rubber squeegees. A second application may be necessary in deep cracks or joints. If seal coating prior to complete drying or set up of crack sealer, sprinkle silica sand (lightly) to promote adhesion to seal coat sealant.
DRYING TIME:	Tack free - 1 hour - Lightly sand in immediate traffic areas. Dry in 4 - 24 hours, depending on weather conditions and thickness of material (except in cases of extreme humidity).
CLEAN UP:	Wash tools in water. Use paint thinner if hardened.
STORAGE:	CAUTION - Keep from freezing. Do not store in direct sunlight or where temperatures exceed 100F.
PACKAGING:	Five gallon pail / 55 Gallon Drum
COLOR:	Black

MSDS sheet available upon request

There are no expressed or implied warranties covering application