



DATA SHEET SPECIFICATIONS

#325 Asphalt Tack Emulsion

DESCRIPTION:	An Anionic Petroleum Asphalt based product used to create a bond between fresh asphalt paving material and existing asphalt or concrete material. Also used to rejuvenate old asphalt pavements.
FEATURES & BENEFITS:	Creates a strong and long lasting bond that helps prevent water and other liquids from reaching the structure of the pavement.
MATERIAL PREPARATION:	When used as a binder no preparation should be necessary. When using to rejuvenate pavement it is recommended that a percentage less than 50% water be added to material for dilution. May need to heat material in order to liquify.
APPLICATION:	Should be done by means of a tack broom, or a tack rig. Both of which can be obtained through GoldStar.
WEATHER LIMITATIONS:	Application should be postponed if wet or freezing weather is expected 24 hours following application. On hot days, pavement should be misted with a fog system prior to application.
COLOR:	Jet Black color upon drying.
CLEAN UP:	Use warm water with an emulsifying cleaner.
STORAGE:	Keep from freezing. Do not store in direct sunlight or where temperatures exceed 100°F.
PACKED:	5 gallon pails, and 55 gallon drums, Delivery available.

*MSDS sheet available upon request
There are no expressed or implied warranties covering application*