



## DATA SHEET SPECIFICATIONS

---

### POLY OIL SEAL # 330

---

- PRODUCT:** Oil spot primer.
- DESCRIPTION:** A quick drying modified barrier coating, formulated to coat and promote adhesion over oil, grease, and gasoline spots or chemical stains prior to the application of coal tar and asphalt sealer on asphaltic surfaces. Can be used over all type of hot patched areas or oil contaminated cracks. Easy to use on parking lots, driveways, airport runways, traffic safety islands, or any asphalt surface.
- SURFACE PREPARATION:** Surface areas to be treated must be free from dirt and dust. Scrape excessive build-up of oil, grease, or any other chemical stain spots. Lightly burn off excessive build-up.
- APPLICATION:** Mix well before using. Use full strength on heavy oil spots. Reduce 1 to 1 or 1 to 2 with water, depending on the build-up of oil, grease, and other stains. Can be applied with suitable spray machine, push broom. Brush or roller.
- COVERAGE PER GALLON:** 300-400 square feet per diluted gallon.
- CAUTION:** Wash tools in water. Use a suitable paint thinner if material has dried. Keep from freezing. Do not store in direct sunlight or where temperature exceed 100F. Container should be closed when not in use. Keep out of the reach of children.
- PACKAGING:** Available in 5 gallon buckets and 55 gallon drums.

MSDS sheet available upon request

There are no expressed or implied warranties covering application.