

Product Information

1354 Jet Way, Perris, CA 92571 * 951-940-1610 Phone / 951-940-9192 Fax

6700 On-Line Traffic Marking

DESCRIPTION

Vista's On-Line is a 100% acrylic, lead-free premium grade waterborne traffic and line marking paint specially manufactured and formulated for optimal adhesion and durability. Designed with a special sheen to enhance durability, weather resistance and resistance to dirt pick up.

Product Advantages: Product will not crack, remains flexible over time, is durable, easy to apply and can be applied by air and airless spray equipment. Requires no thinning, is pre-strained and is environmentally safe and user friendly.

RECOMMENDED USES

On-Line is designed for use as traffic marking, legend identification work, instructional markings on roadways, crosswalks, sidewalks, curbs and parking lots. A multi-surface product suitable for application on fully cured traffic-bearing surfaces such as Portland cement concrete, asphalt, and previously painted surfaces.

COLORS

White, Red, Yellow, Blue, *Green, *Black. *Colors tinted in A base at individual stores.

PACKAGING

One and five gallon containers

SURFACE PREPARATION

•Surface must be clean, dry and free from dirt, oil, grease, carbons, wax, loose or peeling paint or contaminants that may interfere with adhesion. Pressure wash using degreasers or TSP, etching, bead or sand blasting is a recommended method of removal of any/all dirt deposits prior to application.

•New asphalt or top sealed asphalt surfaces should ideally be allowed to thoroughly cure before striping. Place a small inconspicuous test strip to determine if surface of asphalt has cured sufficiently to paint. On-line is not recommended over water soluble top sealers.

APPLICATION

Apply by brush, roller or spray. If sprayed, conventional or airless equipment may be used. Spray equipment must be designed to resist corrosion from constant contact with water. Do not paint during extreme cold, frost, fog, or damp weather conditions. Recommended application temperature ranges 50-90° F. Do not apply below 50° F or if rain is expected within 24 hours.

Safety Precautions: When using this product where high foot traffic areas exists and may become slippery when wet, aggregate such as clean sand or antislip additives should be added if non-skid characteristics are desired.

COVERAGE

Theoretical: 315 lineal feet per gallon at 15 mils (wet) / 6 mils (dry) with a 4" stripe; 105 square feet per gallon 15 mils (wet) / 6 mils (dry). Overall coverage will depend on method of application and surface conditions of substrates.

SUGGESTED MIL THICKNESS

Wet: 12 - 15 mils

Dry: 9 - 11 mils

THINNING

Not recommended. If thinning is required, thin only with clean water. Any water added will slow the dry time.

CLEAN UP


Rinse spray equipment and tools promptly with warm soapy water.

PRODUCT MIXING

Important! Agitate or stir before using product to allow for uniform consistency of paint.

REVISED 01.07

To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance and offered in good faith. All technical information is subject to change without prior notice. This product is guaranteed to give satisfactory performance if applied and used in accordance with the label instructions. Any liability shall be limited to a refund of the purchase price, or replacement of this product. This warranty does not include labor or cost of labor for the application of any coating. All express and all implied warranties are hereby disclaimed and excluded including all implied warranties of fitness for a particular use and merchantability. Final determination of the suitability of product or intended use is the sole responsibility of the user. Additional information may be obtained from your local sales representative.



Product Information

1354 Jet Way, Perris, CA 92571 * 951-940-1610 Phone / 951-940-9192 Fax

6700 On-Line Traffic Marking

(CONTINUED)

SPECIAL NOTES

• The presence of concrete sealers or efflorescence on new concrete may interfere with adhesion and should be removed - see section of surface preparation. • On-Line Traffic and Line Marking products are formulated for airless spray without thinning at ambient temperatures above 50° F. Most typical working pressures are 1500 - 2700 psi, using a .015 - .019 tip size in walk behind machines. 50 to 100 mesh filters at the gun are recommended. • Product limitations - not recommended for immersion service.

PRODUCT APPLICATION

(x) Brush (x) Conventional Spray .055-.070

(x) Roller (x) Airless-Tip Size .015-.023

Note: Tip sizes may vary depending on type of equipment used and manufacturer's specs. It is recommended a small test stripe be done in an inconspicuous area for desired application requirements. Helpful Hint: Due to the fast drying nature of the product, it is suggested that before application you may want to add approximately 16oz of clean water through the opening at the top of the pail. The water will then float at the surface and act as a seal to help prevent product skinning at the surface level. This method is highly recommended when both spraying and prior to storing the materials at the end of a job. Be sure the closure cap and lid are tight and secured before storing product.

STORAGE CONDITIONS

Store in dry well-ventilated area. Storage temperatures should be between 40° F and 90°. Do not Freeze. Shelf life is recommended at 12 months.

COMPOSITION

<u>Total Pigment</u>	<u>61.1%</u>
Titanium Dioxide and Extenders	61.1%
<u>Total Vehicle</u>	<u>38.9%</u>
Resin	12.7%
Water	21.9%
Additives and Solvent	4.3%
Weights & Measurements	±3.0%
Solids by Volume	55.9%
Solids by Weight	74.2%
Coatings VOC	92 g/l
Density:	13.9 lbs
Viscosity	88 - 92 KU

STANDARD DRY FORMULAS

- Conforms to Federal Specification TT-P 1952B.
- Field Test: Tack-free dry 5 minutes, dry time is 15-20 minutes and can dry to no-tracking in 30 minutes to one hour, maximum without beads, depending on wet film thickness and ambient conditions.
- Drying Schedule: No traffic pick up, at 15 mils wet, without beads, 75 minutes, (ASTM D711) maximum. Dry times will be extended at increased humidity above 80% and temperature below 50° F.

REVISED 01.07

To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance and offered in good faith. All technical information is subject to change without prior notice. This product is guaranteed to give satisfactory performance if applied and used in accordance with the label instructions. Any liability shall be limited to a refund of the purchase price, or replacement of this product. This warranty does not include labor or cost of labor for the application of any coating. All express and all implied warranties are hereby disclaimed and excluded including all implied warranties of fitness for a particular use and merchantability. Final determination of the suitability of product or intended use is the sole responsibility of the user. Additional information may be obtained from your local sales representative.